

SERVO MOTOR TYPE
STABILIZER



Humer
Cabinet (3/3)
60KVA

Characteristics

- » International Standards
- » Multi design
- » Full Warranty
- » LCD display and Central processing CPU Unit
- » Smooth Regulating Process
- » Over Voltage Protection
- » Low Voltage Protection
- » Electrical Overload Protection
- » Over Temp Protection

Technical Specification

TECHNICAL DATA

Product Model	Humer Wallmount Full Automatic Voltage Stabilizer	
Output Voltage	Voltage Regulation Accuracy	380V± 4%
	Low-Voltage Protection	340V±7V (Adjustable)
	Over- Voltage Protection	420V±7V
The Input Voltage	270-430V	
Efficiency %	0.9	
Voltage Regulation Speed	<1s(Voltage Fluctuation ≥ 10%)	
Frequency Hz	50/60Hz	
Waveform Distortion	No Additional distortion	
Withstanding Voltage	1500V/1Min	
Temperature rise	<+60°C	
Environment Temp.	-5°C - + 40°C	

PROs

- ▶ Smooth stabilization
- ▶ Stable and continuous voltage
- ▶ High accuracy

CONs

- ▶ Lower speed of voltage regulation
- ▶ Easy to induce contact spark
- ▶ Easy to wear out the carbon brush