

POWER MAXMA

MU803LF

3KVA

1:1 phase PF: 0.8



Control Panel

Features

■ High reliability design

· Double Conversion on-line design, which makes the output a pure sine wave source with tracking frequency, phase-lock and voltage regulation, low distortion and without power fluctuation interference, providing the load with more comprehensive protection.

■ Strong protection for load

· Built-in isolation transformer, strong anti-interference ability, provides more comprehensive protection.

■ Wide input range

· Wide input voltage range up to :165~275Vac, avoid frequently switching to battery mode, which adapt to the areas with harsh environment.
· Wide input frequency range, ensure all types of fuel generators connected work stable.

■ Optimization of high-performance battery

· Advanced floating switching and charging technology maximums the activation of the battery, thus saves the charging time and extends the battery life.

■ Battery cold start function

· The UPS can be start directly by battery group when no utility access in, which meets the emergent needs of user.
· Strong cold start ability, which can do the cold start operation when full load.

■ Comprehensive and reliable protection

· Self-diagnosis function before start-up, avoid the risks that the failure may lead to.
· The multi-protections such as overload, short-circuit, over-temperature, battery under voltage, battery over-charge and so on greatly ensure the system stability and reliability.
· Built-in static electronic bypass switch, when UPS fails, it can transfer to bypass mode and continue to provide power for load by AC.
· DC start function. The UPS can be started directly without AC, which meet the emergent needs of the user.

■ User-friendly network management

· Communication with computer can be realized by RS232 with corresponding monitoring software. The various parameters can be shown on the communication interface.
· External SNMP adapter. The UPS with remote network management capability can provide real-time data for communication and management through a variety of network management systems.



- 1.RS232 port
- 2.FAN
- 3.Input breaker
- 4.Connection box
- 5.Entrance hole
- 6.Active wheel

Rear Panel

Technical Specifications:

MODEL	MU803LF
Capacity (VA/Watts)	3kVA/2.4kW
INPUT	
Nominal voltage	220/230Vac
Operating voltage range	165 ~ 275Vac
Operating frequency range	50/60Hz (± 5%)
Power factor	> 0.97 (with filter)
Max. input current(A)	14
OUTPUT	
Output voltage	220Vac(± 0.5%) / 230Vac(± 0.5%)
Output frequency	50/60Hz(± 0.5%)
Crest factor	3:1 (max)
Efficiency	1~8kVA: 85% online 10~15kVA: 90% online
Harmonic distortion (THD)	<1.5%(linear load)
BATTERY	
Battery voltage	48Vdc or 192Vdc
SYSTEM FEATURES	
Transfer time	0 ms (Line mode→ Battery mode)
Overload	>125% : 1min, >150%: 200ms
Communication interface	RS232, SNMP(optional), Dry contact (optional)
ENVIRONMENTAL	
Operating temperature	0 ~ 40°C
Storage temperature	-25°C ~ 55°C
Humidity range	0 ~ 95% (non-condensing)
Altitude	<1500m
Noise level	<55dB
PHYSICAL	
Dimension W × D × H (mm)	200 × 608 × 538 (48Vdc/Battery) 230 × 580 × 720 (192Vdc/Battery)
Net weight (kg)	62/54
STANDARDS	
Safety	IEC/EN62040-1; IEC/EN60950-1
EMC	IEC/EN62040-2; IEC61000-4-2; IEC61000-4-3; IEC61000-4-4; IEC61000-4-5; IEC61000-4-6; IEC61000-4-8

Specifications are subject to change without prior notice.